

LINEA TAB



ESPECIFICAÇÕES TÉCNICAS

Processador	32-bit ARMTM CortexTM - microcontrolador baseado M3
Compatibilidade	Apple iPod 4 ou 5 / iPhone 4 ou 5 / iPhone 5S
LED	4 LEDs para o estado da bateria
Áudio	Electro-Magnetic Buzzer
Certificações	CE, FCC, PCI PTS 3.x, a Apple ® MFI
Ambiental	-10°C a +40°C / 5% a 90% RH : -20°C a +50°C / 5% a 90% RH
Leitores	1D*JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128(EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISMN-ISSN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey; Postal code: Chinese Post, Korean Postal Authority code; Composite codes, MicroPDF417, PDF417-2D*: Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, Code 93, UCC/EAN-128, GS1 Databar, Matrix 2 of 5, Code 11, Industrial 2 of 5, Standard 2 of 5, Plessey, MSI-Plessey; PDF417, Data Matrix (ECC200, ECC000, 050, 080, 100, 140), QR Code
Teste de queda	1,5 m
Peso	115 g
Dimensões	51 x 128 x 45 mm (2 x 5 x 1.8 inch)

